

Title

Belt Drive System with Automatic Belt Tension Control

5 Field of the Invention

The invention relates to belt drive systems and more particularly to engine belt drive systems having automatic belt tension control.

10 Background of the Invention

Most engines used for automobiles and the like include a number of belt driven accessory systems that are necessary for the proper operation of the vehicle. The accessory systems may include an alternator, air conditioner compressor and power steering pump.

The accessory systems are generally mounted on a front surface of the engine. Each accessory having a pulley mounted on a shaft for receiving power from some form of belt drive. In early systems, each accessory was driven by a separate belt that ran between the accessory and the crankshaft. With improvements in belt technology, single serpentine belts were developed and are now used in most applications. Accessories are driven by a single serpentine belt routed among the various accessory components. The serpentine belt is driven by the engine crankshaft.

Since the serpentine belt must be routed to all accessories, it has generally become longer than its predecessors. To operate properly, the belt is installed with a pre-determined tension. As it operates, it may stretch slightly. This results in a decrease in belt tension, which may cause the belt to slip. Consequently, a belt tensioner is used to maintain the proper belt tension

as the belt stretches during use. A belt tension may be controlled by movement of pulleys as well as through the use of tensioners.

Control systems are known which allow a user to adjust a belt tension during operation of the system. These systems generally use a cylinder or other mechanical device to adjust a drive wheel position. The control system may also adjust a belt tension in response to belt speed.

Representative of the art is Japanese Publication No. 2001-059555 to Denso which discloses a belt transmission system to control slipping of a belt by computing a slip factor from a detection value from a first and second tachometer, the first tachometer detecting an engine speed and the second tachometer detecting an auxiliary module speed.

Also representative of the art is US 5,641,058 (1997) to Merten et al. which discloses an invention which employs pressure and displacement sensors for the automatic monitoring and adjustment of endless belts by movement of drive and return wheels.

The prior art does not allow active control of belt tension to reduce belt slip while increasing belt life by setting a low belt tension when low tension is all that is required, but increasing tension momentarily and temporarily when such is necessary during transient conditions to prevent belt slip and associated noise.

What is needed is a belt tension control system having sensors for detecting a belt operating condition. What is needed is a belt tension control system having a control module for using belt operating condition signals to actively control an actuator. What is needed is a belt tension control system for increasing a belt life by

actively controlling a belt tension. What is needed is a belt tension control system capable of anticipating and preventing a belt slip noise event. The present invention meets these needs.

5

Summary of the Invention

The primary aspect of the invention is to provide a belt tension control system having an actuator controlled by a control module for moving a pivoted pulley to adjust a belt tension.

Another aspect of the invention is to provide a belt tension control system having sensors for detecting a belt operating condition.

Another aspect of the invention is to provide a belt tension control system having a control module for using belt operating condition signals to actively control an actuator.

Another aspect of the invention is to provide a belt tension control system for increasing a belt life by actively controlling a belt tension.

Another aspect of the invention is to provide a belt tension control system capable of anticipating and preventing a belt slip noise event.

Other aspects of the invention will be pointed out or made obvious by the following description of the invention and the accompanying drawings.

The invention comprises a belt drive system for automatically controlling a belt tension. The system comprises an actuator controlled by a control module. The actuator operates on a pivoted pulley. A belt is trained about the pivoted pulley as well as other pulleys driving various accessories. A series of sensors in the system

detect a belt condition including a belt tension. Sensor signals are transmitted to the control module. The control module processes the signals and instructs the actuator to move the pivoted pulley, thereby increasing or decreasing a belt tension. A feedback loop from the sensors to the control module allows the belt tension to be continuously monitored and adjusted many times per second. The system may actively control a belt tension by anticipating a system condition to prevent a belt noise by comparing sensor signals to a system model stored in a control module memory.

Brief Description of the Drawings

The accompanying drawings, which are incorporated in and form a part of the specification, illustrate preferred embodiments of the present invention, and together with a description, serve to explain the principles of the invention.

Fig. 1 is a schematic view of the inventive system.

Fig. 2 is a schematic diagram of the closed loop control philosophy.

Fig. 3 is a control algorithm diagram for the inventive system.

Detailed Description of the Preferred Embodiment

Fig. 1 is a schematic view of the inventive system. The system anticipates and prevents belt slip in front end accessory drive systems thereby decreasing system noise and increasing belt life. The extent to which a belt may slip is dependent primarily on load and belt tension. A surface coefficient of friction on a belt and pulley(s) also plays a role. Belt slip is most readily identified by noise

emitted by the belt during operation. Belt slip may also result in premature belt failure without causing noise, but as a result of increased belt temperature through friction between a belt and a pulley. Friction causes a belt temperature to rise to levels that are detrimental to long belt life. Belt slipping most often occurs during transients when system conditions are rapidly changing, for example engine accelerations and decelerations. To prevent this from occurring, the instant invention allows a belt operating condition, including a belt tension to be detected, analyzed and rapidly adjusted in order to prevent a belt slip condition.

The inventive system generally comprises a number of accessories being driven by an endless belt or drive member 6. The accessories driven by the belt are mounted to a front surface or surfaces of a vehicle engine. The accessories and belt may also be mounted to a frame, wherein the frame with the belt and accessories is then mounted as a complete unit to an engine surface.

The accessories comprise an alternator 2 (ALT) and pulley 4, idler 8 (Idr), power steering pump 10 (PS), air conditioner 12 (AC), water pump 14 (WP), and crankshaft pulley 16 (CRK), each accessory having a pulley engaged with the belt. The crankshaft pulley drives the belt in direction D, thereby driving the accessories. The pulley and belt may have any profile known in the art, including v-belt, multi-ribbed or toothed.

Alternator 2 comprises a frame that is pivotably mounted to an engine surface or base (not shown) at pivot 30. Alternator 2 also comprises arm 38 that is engaged at one end by actuator 20. Pivot 30 allows the alternator and thereby the pulley to be pivoted about pivot 30 by a

movement of actuator 20. A pivoting movement of alternator 2 allows a belt tension to be adjusted.

Control module 18 comprises a computer processor capable of receiving and processing sensor signals received from sensors 22, 46, 48, and 58. It also generates and transmits control signals for controlling an actuator 20 movement and relative position. Sensor 22 is a load cell for detecting a load caused by a belt tension acting on the alternator arm 38. Sensor 46 detects a belt tension by detecting a load exerted on the idler 8 by a belt 6. Sensor 48 detects a displacement of the actuator 20. Sensor 58 detects a rotational speed of crankshaft pulley 16, which also equates to engine speed. Each sensor may comprise an analog or digital configuration, depending on a users needs.

Control module 18 is connected to sensors 22, 46, 48, 58 by wires 60, 63, 62, and 64 respectively. It is also electrically connected to actuator 20 by wire 61. The system may include sensors in addition to those described above. The additional sensors may provide other signals to the control module for adjusting a belt condition including ambient temperature and belt alignment. Each sensor may also comprise a RF transmitter with the control module comprising an RF receiver, thereby eliminating the need for physical connectors such as wires between the sensors and the control module.

Control signals are transmitted by control module 18 to actuator 20 through wire 61. Actuator 20 may comprise an electric motor, solenoid, or hydraulic cylinder or other form of mechanism known in the art that is capable of effecting a displacement or movement of arm 38 upon receiving a control signal from the control module.

Control module 18 may be programmable by a user thereby allowing a user to adjust operating parameters. The control module may also be 'hard-wired' and therefore unprogrammable by a user in the field. In either case the control module must be initially programmable to allow an instruction set to be initially loaded by means known in the art.

In operation, belt 6 is entrained on the drive system pulleys as shown in Fig. 1. Sensors 22, 46, 48, and 58 are installed at predetermined positions on the belt drive system. Sensor 46 detects a belt tension at idler 8. This is referred to as the "tight" side of the belt with respect to the alternator. Sensor 22 detects a load that is a function of a belt tension acting upon alternator pulley 4 and through a moment arm having a length L extending from pivot 30 to a point on arm 38. Sensor 48 detects a relative position of actuator 20. Sensor 58, which may comprise a tachometer, detects a crankshaft rotational speed.

Fig. 2 is a schematic diagram of the closed loop control philosophy. Each sensor 22, 46, 48, and 58 transmits signals proportional to the load, tension, displacement or speed of the belt to the control module 18. The signals received by the control module from each sensor are compared to measured and calculated operating parameters or to parameters stored in a control module memory, more particularly, certain parameter reference values. The control module 18 then generates a control signal in response to the comparison of the stored reference parameters to the signal parameters. The resultant control module signal is transmitted to actuator 20 which moves to vary an alternator pulley position by

partially rotating the alternator arm 38 about pivot 30. Movement of alternator 2 either increases or decreases a belt 6 tension. The change in a belt or engine operating condition, or increase or decrease in belt tension, is sensed by each sensor 22, 46, 48, 58 which then causes the cycle to repeat. This closed-loop system allows the control module to quickly and accurately control a belt tension in response to a measured belt tension. This allows 'real-time' adjustment of belt tension based upon operational need.

This represents a significant improvement over the prior art by increasing a belt life by allowing a belt tension to be maintained at a nominal level for most operating conditions, but then allowing a belt tension to be temporarily changed to prevent a belt slip or noise from occurring during transient conditions.

The magnitude of the change in a belt tension is adjustable based upon the operating condition prevailing at the time. For example, it may be necessary to increase a belt tension by 200N in certain high transient load conditions, while in other cases an increase of only 100N may be sufficient to prevent a belt slip or belt slip noise from occurring. In either case, the control module analyses the sensor signals and signals the actuator to set an appropriate arm 38 position and thereby an appropriate belt tension. Once the transient condition has passed the actuator position and hence belt tension is changed back to a nominal operating value. Typically the transients correspond to engine accelerations/decelerations and have durations on the order of a few seconds.

Measurable characteristics of the engine and belt drive system which serve to anticipate and quantify

transient events may be programmed into the control module. These may include differential loads on each sensor based upon their respective locations in the system. These parameters may also include engine acceleration, and ambient temperature. As the belt and engine parameters vary, they are measured and transmitted by the sensors and received by the control module processor. The processor processes these sensor signals and sends a control signal to activate the actuator to either increase or decrease a belt tension before a belt slip or noise generating event occurs.

By way of example, if a transient condition such as an engine acceleration is imminent, the control module may instruct the actuator to adjust a position to maintain or increase a belt tension before a belt slip occurs. For example, for an engine acceleration of 6000 RPM/sec, the acceleration duration is approximately 1 second. The required processing time for one complete cycle through the control loop in Fig. 3 is approximately 10-20 milliseconds. One cycle comprises the time required to sense the system condition, compute an appropriate actuator movement, move the actuator and then measure the changed system condition. One can readily appreciate this allows the system to operate at a rate of 50 to 100 adjustments per second, sufficient to control belt slip and belt tension. Consequently, a real-time, active control of a belt tension and thereby of a belt slip noise is realized by the instant invention.

To further enhance the active control feature of this invention the control module may be integrated with a vehicle central processing unit (CPU). In this embodiment the vehicle CPU is programmed to analyze engine and belt

operating conditions that would be expected to cause belt noise. The engine operating conditions would comprise variables such as engine speed, engine acceleration, engine temperature, and ambient temperature. The vehicle CPU
5 receives and processes signals for each variable noted above plus others including throttle position, transmission gear, electrical load, rotational speed of various accessory pulleys and so on. The system may also act to prevent a belt slip when a differential speed between the
10 belt and an accessory pulley exceeds a predetermined value of any selected variable, including pulley speed. On receipt of a command signal from the vehicle CPU, through wire 70, the control module 18 signals actuator 20 to move if the control algorithm required such movement, thereby
15 increasing or decreasing a belt tension. This would occur concurrently with the control module's analysis of the sensor signals. The vehicle command signal is reconciled with the control module control signal to avoid conflicting signals being transmitted to the actuator. In this
20 embodiment the control module would not have a separate presence, instead being integrated within the vehicle CPU, requiring only a small portion of the overall vehicle CPU processing and memory capacity.

In another embodiment, the control module receives a
25 plurality of signals of the type noted above from the vehicle CPU through wire 70. In this embodiment the control module is tasked with processing the vehicle CPU signals along with the sensor signals to generate a control signal. The control signal is transmitted to the actuator
30 to adjust a belt tension.

In yet another embodiment the system may operate in an open loop mode whereby a control command is input to the

control module. The control command may be pre-programmed, or such command can be input by an outside user, or received from another source such as the vehicle CPU. The control module processes the control command to generate a control signal that is transmitted to the actuator. No feedback is received from a separate sensor, so the system achieves an equilibrium state based on the changed position of the actuator. This embodiment allows a user to adjust a belt tension independently of the system operating parameters. The control module may also compare the control command to a known set of values stored in a memory in order to prevent overstressing the system causing premature belt failure.

Fig. 3 is a control algorithm diagram for the inventive system. The algorithm comprises a closed loop. Variables used in the diagram include "Ts" meaning alternator theoretical slack side tension required to prevent slip. Other variables are defined herein.

At 1001, inputs to the control module include an alternator hubload from sensor 22, an idler hubload from sensor 46, and an engine speed from sensor 58. These measured parameters are used to calculate an alternator torque, an alternator Tsm and alternator Ttm. "Hubload" refers the load imposed on a pulley by a belt tension.

The equations are:

$$T_{tm} = \frac{F_{ldr}}{2\sin(\frac{\theta_{ldr}}{2})}$$

and,

$$T_{sm} = \frac{H_{Alt} \frac{L_1 + L_2}{L_1}}{\sin(\frac{\theta_{Alt}}{2})} - T_{tm}$$

and

$$T_{Alt} = R_{Alt} (T_{tm} - T_{sm})$$

5 where,

Tsm = Alt slack side tension calculated from measured data

Ttm = Alt tight side tension calculated from measure data

F_{ldr} = Force measured at the idler

H_{Alt} = Alternator hubload

L₁ = Distance from pivot to Alt pulley center

L₂ = Distance from Alt pulley center to load cell

θ_{ldr} = Idler pulley wrap

θ_{Alt} = Alternator pulley wrap

R_{Alt} = Pitch diameter of alternator pulley

T_{Alt} = Alternator torque

At 1002, the control module determines if the alternator is loaded or unloaded, based upon alternator Tsm and Ttm calculated at 1001. The "alternator load" measurement comprises the electrical load imposed upon the alternator by operation of the vehicle of which it is a part.

If the alternator is loaded, at 1003 the control module calculates the required alternator Ts, or slack side tension, for a loaded system. In this case the loaded system includes a loaded power steering pump, air conditioner, water pump and alternator at the specific engine speed. At 1007, the control module determines if the alternator Tsm from 1001 is less than the calculated alternator Ts at 1003, for this condition. If the answer is "yes" then the control module will send a signal to

increase the alternator hubload, see 1008, by activating actuator 20. If the answer is "no" the control module sends a signal to decrease the alternator hubload, see 1009, by activating actuator 20. Sensor 22 provides actuator position signals at 1010 in response to a movement of the actuator.

At 1010 a signal is received by the control module from sensor 48 to determine if the actuator has reached either of its travel limits. If the answer is "yes", a warning signal will be generated to indicate either excessive belt stretch or breakage, see 1011. If the answer is "no" then the loop repeats beginning with 1001. Sensor 48 and the associated travel limits are set after the belt is installed and properly tensioned.

Returning to 1002, if the alternator is not loaded, the control module determines whether or not the air conditioner is loaded, see 1004. In this case "air conditioner load" refers to the air conditioner compressor being in service.

If the air conditioner is loaded, at 1005 the control module calculates the required alternator T_s for a loaded system. The loaded system in this case includes a loaded power steering pump, air conditioner, and water pump under load at the specific engine speed with the alternator unloaded. At 1007, the control module determines if the alternator T_{sm} from 1001 is less than the calculated alternator T_s at 1005, for this operating condition. If the answer is "yes" then the control module will send a signal to increase the alternator hubload, see 1008, by activating actuator 20. If the answer is "no" the control module sends a signal to decrease the alternator hubload, see 1009, by activating actuator 20. As described above,

at 1010 a signal is received by the control module to determine if the actuator has reached either of its travel limits. If the answer is "yes", a warning signal will be generated to indicate either excessive belt stretch or breakage, see 1011. If the answer is "no" then the loop repeats beginning with 1001.

Returning to 1004, if the air conditioner is not loaded the control module calculates the required alternator Ts for the system with the loaded power steering and water pump loaded at the measured engine speed, see 1006. At 1007 the control module determines if the measured alternator Tsm is less than the calculated alternator Ts for this condition. If the answer is "yes" then the control module will send a signal to increase the alternator hubload, see 1008, by activating actuator 20. If the answer is "no" the control module sends a signal to decrease the alternator hubload, see 1009, by activating actuator 20. Sensor 22 provides actuator position signals at 1010 in response to a movement of the actuator. As described above, at 1010 a signal is received by the control module to determine if the actuator has reached either of its travel limits. If the answer is "yes", a warning signal will be generated to indicate either excessive belt stretch or breakage, see 1011. If the answer is "no" then the loop repeats beginning with 1001.

One can appreciate that the system described herein can include additional belt driven accessories, including an air compressor or mechanical fuel pump. It may also include multiple belt trains, each driven by a crankshaft pulley and each comprising a pivoted pulley and actuator.

Although a single form of the invention has been described herein, it will be obvious to those skilled in

the art that variations may be made in the construction and relation of parts without departing from the spirit and scope of the invention described herein.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000